




Side Sealing Bag

PARKINS
PLASTIC MACHINERY CO.,LTD



SIDE SEALING BAG OTHERS

COMPANY PROFILE	02
BJAT+PLD	05
BJAT+S	06
BJAT+WS	08
BJAFO+S / BJA+3CFO	09
BJA+LS	10
BJAG+S / BJAG2+S	11
BJP 3T / 5T	12

COMPANY PROFILE

COMPANY PROFILE

02

PARKINS PLASTIC MACHINERY CO., LTD.


PARKINS PLASTIC MACHINERY CO., LTD. was established in 1976 under the leadership of President C.I. Lin. PARKINS has successfully developed the most comprehensive range of plastic bag sealing and cutting machines with 40 years of experiences and that makes it to be rewarded as one of the leading manufacturers in Taiwan plastic machinery industry. PARKINS' machines have been sold in over 60 countries, and received full approval from customers over the world.

Based on PARKINS' the advanced bag making concepts, we are equipped with high-quality spare parts, and advanced devices to increase product functionality; at the same time maintaining the stability and quality during bag making process. We adopt modern production management, and all parts are precision machined by sophisticated CNC equipment to ensure machine accuracy and parts interchangeability.


"PARKINS" written in Chinese as "BAI-JIU" implicates "Everlasting Century". We will uphold our principle of sustainability and keep striving for more enhanced machines and superior technical services for our valuable customers.

We manufacture a variety of bag making machines. Products including High-Speed T-shirt Bag, Perforating Bag-on-roll Garbage Bag, Bottom-Sealing Bag, Heavy-Duty Bag, Laundry-Bag, Side-Sealing Bag, Calendar Bag, EVA or PE material deposable Gloves, and etc..

Kindly refer to our website: www.parkins.com.tw for more information. Please do not hesitate to email or call us for any further questions or inquiries. We will provide our most competitive quotations and delivery time to meet your requirements and needs. We believe that you will discover the machine that surpasses your needs.



23.5°N Tropic of Cancer Solar Exploration Center





PARKINS PLASTIC MACHINERY

www.parkins.com.tw

PRODUCTS
PARKINS PLASTIC MACHINERY CO., LTD.



BJAT+PLD

Patch Handle, Loop Handle & Die Cut Handle Bags
Making Machine with Fully Automatic Servo Control.



SPECIFICATIONS >>

MODEL	BJAT+PLD 32"
Bag Width (mm)	250 - 650
Bag Length (mm)	250 - 650
AC Driving Motor (HP)	2
Thickness (micron / sheet)	45 - 90
Power Required (kW)	15.3
Machine Dimensions (L*W*H cm)	930 x 285 x 195
Main Packing Measurement (L*W*H cm)	686 x 225 x 223
Sub (L*W*H cm)	240 x 225 x 160


Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

FEATURES >>

- Servo control system, easier for size adjustment and maintenance.
- Corners of bags are reinforced.
- Automatic sensor control when abnormalities occur, machine will stop automatically, abnormal function parts and reasons will be shown on control screen.

BJAT+S

Edge Sealing & Cutting Machine with Servo Control



BJAT+S

06

PARKINS PLASTIC MACHINERY CO., LTD.

FEATURES >>

- The machine is fed by servo motor, providing small tolerance on bag dimensions, and easy maintenance.
- Machine can heat-sealing and cutting many kinds of appearance for bags as following.


ILLUSTRATION >>



Inside Lip A



Inside Lip B




Inside Lip C




Inside Lip D



Standard




Standard Lip



Ous Side Lip A



2 Inside Lip




Gusset Lip



Gusset Inside Lip



Center Slit


SPECIFICATIONS >>

MODEL	BJAT+S 20"	BJAT+S 28"	BJAT+S 32"
Max. Sealing Width mm (inch)	457 (18")	660 (26")	762 (30")
Max. Sealing Length mm (inch)	76 - 762 (3" - 30")	76 - 762 (3" - 30")	76 - 762 (3" - 30")
Thickness (micron / sheet)	15 - 80	15 - 80	15 - 80
Length Tolerance (mm)	±1	±1	±1
Production Rate (pcs / min)	max.200	max.200	max.200
AC Driving Motor (HP)	2	2	2
Heater Capacity (kW)	1.5	2.2	2.8
Power Required (kW)	7.5	8.2	8.8
Machine Dimensions (L*W*H cm)	300 x 135 x 190	300 x 155 x 190	300 x 165 x 190
Machine Weight (kg)	1300	1600	2000
Packing Measurement (L*W*H cm)	310 x 140 x 210	310 x 160 x 210	310 x 170 x 210
Gross Weight (kg)	1600	1900	2300

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

BJAT+WS

Wicket Bag Making Machine with Fully Automatic Servo Control

SPECIFICATIONS >>

MODEL	BJAT+WS 800	BJAT+WS 1000
Max. Sealing Width (mm)	300 - 350	90 - 330
Max. Sealing Length (mm)	300 - 600	300 - 900
Thickness (micron / sheet)	8 - 50	18 - 70
Production Rate (pcs / min)	PE:300 / PP:200 / Chicken:200	PE:300 / PP:200 / Chicken:200
AC Driving Motor (HP)	2	2
Heater Capacity (kW)	1.8	2.8
Power Required (kW)	15	16
Machine Dimension (L*W*H cm)	800 x 216 x 225	800 x 226 x 225
Machine Weight (kg)	2800	3700
Main Packing Measurement (L*W*H cm)	495 x 175 x 225	495 x 225 x 225
Sub (L*W*H cm)	230 x 100 x 185	230 x 180 x 185

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

FEATURES >>

- When abnormalities occur the machine will stop automatically.
- With auto stacker conveyor.
- Wicket type.

OPTIONS >>

- With calendar function.
- With chicken bag function.
- Triangle folding unit with EPC.

BJAT+WS

08

PARKINS PLASTIC MACHINERY CO., LTD.



BJAFO+S / BJA+3CFO

Servo Control Bag Folding Machine

SPECIFICATIONS >>

MODEL	BJAFO+S 4060	BJA+3CFO 4060
Max. Cutting Width mm (inch)	965 (38")	965 (38")
Max. Cutting Length mm (inch)	1.5 (60")	1.5 (60")
Thickness (micron / sheet)	10 - 50	10 - 50
Length Tolerance (mm)	±1	±1
Production Rate (pcs / min)	max.60	max.60
Main AC Driving Motor (HP)	2	2
Power Required (kW)	9.6	9.6
Machine Dimensions (L*W*H cm)	510 x 183 x 180	570 x 240 x 190
Main Machine Weight (kg)	1250	1200
Sub Machine Weight (kg)	1300	1500
Main Packing Measurement (L*W*H cm)	255 x 184 x 180	240 x 185 x 215
Folding (L*W*H cm)	Sub:283 x 195 x 180	370 x 210 x 185
Feeding+Conveyor (L*W*H cm)	-	227 x 227 x 195
Main Gross Weight (kg)	1450	1450
Sub Gross Weight (kg)	1600	Sub1:1800 / Sub2:600

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

FEATURES >>

- With this sealing & cutting machine, each sheet folds automatically. It saves time and labor.
- Depending on width, bags can be folded in three or four to speed up packing.



BJA+LS

Fully Automatic Servo-Control Plain & Garment Bags
Sealing and Cutting Machine



BJA+LS
10
PARKINS PLASTIC MACHINERY CO., LTD.

FEATURES >>

- Applicable to make bottom sealing bag & laundry bag.
- Operated with an electronic controlled and servo driver to ensure perfect sealing & cutting.
- The machine stops as soon as abnormalities occur.

SPECIFICATIONS >>

MODEL	BJA+LS 32	BJA+LS 40
Max. Cutting Width mm (inch)	762 (30")	965 (38")
Max. Cutting Length m (inch)	1.7 (70")	1.7 (70")
Thickness (micron / sheet)	12 - 50	12 - 50
Length Tolerance (mm)	±1	±1
Production Rate (pcs / min)	max.120	max.120
AC Driving Motor (HP)	2	2
Heater Capacity (kW)	3.5	4.0
Power Required (kW)	7.6	10.4
Machine Dimensions (L*W*H cm)	686 x 195 x 195	686 x 215 x 195
Machine Weight (kg)	1350	1600
Packing Measurement (L*W*H cm)	230 x 160 x 173	230 x 225 x 215
Gross Weight (kg)	1700	2000

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

BJAG+S / BJAG2+S | Servo Control Glove Bag Making Machine



BJAG+S / BJAG2+S

PARKINS PLASTIC MACHINERY CO., LTD.

FEATURES >>

- The machine is fed by servo motor, providing small tolerance on bag dimensions, and easy maintenance.
- The machine is especially designed for glove type bag making also make record bags, irregular bags and other general bags.

SPECIFICATIONS >>

MODEL	BJAG+S 2030	BJAG2+S 3230
Max. Cutting Width mm (inch)	406 (16")	355 (14") x 2
Max. Cutting Length mm (inch)	762 (30")	762 (30")
Thickness (micron / sheet)	10 - 30	10 - 30
Length Tolerance (mm)	±1	±1
Production Rate (pcs / min)	max.120	max.120
AC Driving Motor (HP)	2	2
Heater Capacity (kW)	2.9	5.8
Power Required (kW)	7.2	10.3
Machine Dimensions (L*W*H cm)	395 x 120 x 150	485 x 150 x 150
Machine Weight (kg)	850	1200
Packing Measurement (L*W*H cm)	230 x 130 x 173	250 x 210 x 190
Gross Weight (kg)	1000	1450

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.

BJP 3T/5T | Manual Punching Machine

BJP 3T/5T
12
PARKINS PLASTIC MACHINERY CO., LTD.




FEATURES >>

- Pressure boosted design incorporates outstanding features of pneumatic quick motion and hydraulic great power output.
- Safety gear: operating the machine must be done by both hands.

SPECIFICATIONS >>

MODEL	BJP 3T	BJP 5T
Pneumatic & Oil Type Capacity (Tons)	3	5
Width Of The Table (mm)	500	700
Equipped 3 model knives	125,145,175	125,145,175
Machine Measurements (cm)	80 x 68 x 188	80 x 88 x 188
Cutting Board Material	PP	PP

Correct specifications depend on the actual model. All specifications are subject to change without prior notice.







PARKINS
PLASTIC MACHINERY CO.,LTD
百久塑膠機械有限公司

嘉義縣水上鄉回歸村北回123號

NO.123 Pei Hui, Hui Kuei Village, Shui Shang Township, Chiayi County, Taiwan.

TEL:+886-5-2358505, 2359505, 2356586 FAX:+886-5-2359463

E-mail: pks8989@ms12.hinet.net / bj8899@ms39.hinet.net

<http://www.parkins.com.tw>

